

ÃÑ°µÔ´µÑέ\$áÁĐ»ÃÑ°´Ù¹;ÁέÍ\$ F-Con/Power Fc/Wolf/Heltech ´έÇÂ AF Wide Band Knock Motinor (ÃÙ¹µέÒÍÒ´¹Ó¹ÁέÍ\$ÁÒáÍ\$ËÃ
áµèµέÍ\$¹Ñ´ÉÁÒÁÀèÇ\$Ë¹έÒ 3 ÇÑ¹µÃÑ°) ÃÒÁÀĐáÍÒÁ´ ´Ñ\$¹Óέ

1. E-Manage ÃÒµÒ´Ù¹ 3,500 °Ò.
2. F-Con S/SZ/IS ÃÒµÒ´Ù¹ 4,000 °Ò.
3. F-Con V-Pro 2.1 ÃÒµÒ´Ù¹ 6,000 °Ò.
¾ÃέÍÁâ»ÃâÁªÑè¹¾ÔàÉÉÉÉÉÉÃÑ°;ÁέÍ\$ F-Con V-Pro 2.1 à´ÍÀì 1000 ¾ÃέÍÁ´Ù¹ + Dyno + Map + Wiring ÃÒµÒ 32,000 °Ò.
4. F-Con Pro 3-3.3 ÃÒµÒ´Ù¹ 7,000 °Ò.
5. Power FC ÃÒµÒ´Ù¹ 6,000 °Ò.
6. Wolf ÃÒµÒ´Ù¹ 8,000 °Ò.
¾ÃέÍÁâ»ÃâÁªÑè¹¾ÔàÉÉÉÉÉÉÃÑ°;ÁέÍ\$ Wolf V-500 ¾ÃέÍÁ´Ù¹ + Dyno ÃÒµÒ 59,000 °Ò. (¹Ñ´ÉÁÒÁÀèÇ\$Ë¹έÒ 7 ÇÑ¹)
7. Haltech ÃÒµÒ´Ù¹ 8,000 °Ò.

à¾ÔèÁàµÔÁ (ÃÒµÒ´Ù¹ ÉÓËÃÑ°;ÁέÍ\$.ÒèäÁè´Ñ´á»ÃâÁªÑè¹´ĐäÁèÃÇÁÃÒµÒ Wiring ¶έÒµέÍ\$;ÒÃ Wiring µÒ´à¾ÔèÁ 2,000 °Ò.
Ò\$àÃÒ°ÃÔ;ÒÃà»ÃÒèÁ¹¶èÒÁ¹έÓÁN¹àµÃxέÍ\$ àªçµÉÁÒ¾Ã¶ »ÃÖ;ÉÓ»Ñ-ÉÒàÃxέÍ\$Ã¶ ã¹ÃÒµÒµØÁ;Ñ¹´έµÃÑ°
µÔ´µέÍ ÃÒÁÀĐáÍÒÁ´ÉÍ¶¶ÒÁà¾ÔèÁµÔÁ ä´έ·Òè µØ³ÁÒè 08-1399-2183 µÃÑ°

=====